

Type SGX BATTERY CABLE



RoHS Compliant

Cables are manufactured to meet current SAE guidelines.

Part Number	AWG	Strand	Insulation Thickness (mils)	Nominal O.D. (inch)	Approximate Net Weight lbs/1M'
SGX206-133	6	7x19/.0136	60	.289	95
SGX204-133	4	7x19/.0169	65	.370	152
SGX202-133	2	7x19/.0218	65	.437	241
SGX201-259	1	7x37/.0175	65	.475	294
SGX2010-259	1/0	7x37/.0195	65	.515	361
SGX2020-259	2/0	7x37/.0222	65	.570	459

PRODUCT DESCRIPTION

Flexible strand bare copper conductor with premium grade XLP insulation.

CONSTRUCTION

Conductor: Flexible Strand Bare Copper
Insulation: Premium Grade XLP

APPLICATIONS

For use in starter or battery ground circuits on boats, cars, trucks, buses, RVs, and tractors in accordance with SAEJ1127. Resistant to acid, abrasion, oils, fuels and fluids

INDUSTRY LISTINGS & STANDARDS

Temperature Range: -40°C to +125°C

INSULATION COLORS

Black

AVAILABLE PUT-UPS

Reels: 500, 1000, 2500, 5000, 10000 feet
Custom Put-ups available upon request

CABLE IDENTIFICATION

ADVANCED DIGITAL CABLE, INC. xx AWG TYPE SGX
125C XLPE SAEJ1127

