

## UL Styles 1007/1569

HOOK UP WIRE



### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including (UL) and CSA.

Part Number	AWG	Conductor		Nominal O.D. (Inch)	Weight, Lbs. /1000ft.
		Strand	Type		
A0724-1T	24	SOLID	TC	.052	2.27
A0724-1	24	SOLID	BC	.052	2.27
A0724-7T	24	7/32	TC	.056	2.55
A0724-7	24	7/32	BC	.056	2.55
A0722-1T	22	SOLID	TC	.057	3.14
A0722-1	22	SOLID	BC	.057	3.14
A0722-7T	22	7/30	TC	.062	3.55
A0722-7	22	7/30	BC	.062	3.55
A0720-1T	20	SOLID	TC	.064	4.49
A0720-1	20	SOLID	BC	.064	4.49
A0720-7T	20	7/28	TC	.070	5.09
A0720-7	20	7/28	BC	.070	5.09
A0720-10T	20	10/30	TC	.068	4.69
A0718-1T	18	SOLID	TC	.072	6.56
A0718-1	18	SOLID	BC	.072	6.56
A0718-16T	18	16/30	TC	.078	6.88
A0718-16	18	16/30	BC	.078	6.88
A0716-1T	16	SOLID	TC	.083	9.78
A0716-1	16	SOLID	BC	.083	9.78
A0716-26T	16	26/30	TC	.091	10.44
A0716-26	16	26/30	BC	.091	10.44
A0714-41T	14	41/30	TC	.106	15.66
A0714-41	14	41/30	BC	.106	15.66
A0712-65T	12	65/30	TC	.153	27.52
A0712-65	12	65/30	BC	.153	27.52
A0710-105T	10	105/30	TC	.178	41.48
A0710-105	10	105/30	BC	.178	41.48

### PRODUCT DESCRIPTION

Tinned or bare copper wire, either stranded or solid, with PVC insulation.

### CONSTRUCTION

Conductor: Tinned or Bare Copper, Solid or Stranded  
 Insulation: Polyvinyl Chloride  
 Insulation Thickness: 0.016" (0.030" for TR-32)

### APPLICATIONS

Internal wiring of appliances.

### INDUSTRY LISTINGS & STANDARDS

UL Style 1007 300V 80°C - 24 AWG-16 AWG  
 UL Style 1569 300V 105°C - 24 AWG -10 AWG  
 CSA Type TR-64 300V 90°C - 24 AWG - 14 AWG  
 CSA Type TR-32 300V 90°C - 12-10 AWG  
 VW-1 Flame Test  
 Gasoline and Oil Resistant II  
 Other: RoHS, FT-1

### COLOR CHART

Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White

### AVAILABLE PUT-UPS

Reels: 500, 1000, 2500, 5000, 10000 feet  
 Drums, Half-Drums  
 Custom Put-ups available upon request

### CABLE IDENTIFICATION

#### 24-16 AWG LEGEND

ADC xx AWG RU AWM STYLE 1007 80C OR AWM STYLE 1569 105C 300V VW-1 E178258 OR CSA TYPE TR-64 90C FT1 LL111578

#### 14 AWG LEGEND

ADC xx AWG RU AWM STYLE 1569 105C 300V VW-1 E178258 OR CSA TYPE TR-64 90C FT1 LL111578

#### 12-10 AWG LEGEND

ADC xx AWG RU AWM STYLE 1569 105C 300V VW-1 E178258 OR CSA TYPE TR-32 90C FT1 LL111578



The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable.

ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice. Rev HU1122

PHONE: (800) 343 2579 • FAX: (828) 389 3922 • WWW.ADCABLE.COM