# **COMMUNICATION & CONTROL** | PVC INDUSTRY EQUALS











AWG	COND	STRAND	PART NO.	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT /
				INCH	mm	INCH	mm	1M'
24	1 Pr	7x.0076 TC	4-2402* Equal to Belden™ 9841	.035	.89	.232	5.89	37
	2Pr	7x.0076 TC	4-2422* Equal to Belden™ 9842	.035	.89	.340	8.64	55
22	2	7x30 TC	22002TSD Equal to Belden™ 8761	.025	.64	.175	4.44	20
	3	7x30 TC	22003TSD Equal to Belden™ 8771	.025	.64	.187	4.75	24
	4	7x30 TC	22022TSD Equal to Belden™ 8723	.020	.51	.160	4.06	24
	6	7x30 TC	22033TSD Equal to Belden™ 8777	.034	.86	.228	5.79	37
20	2	7x28 TC	20002TSD Equal to Belden™ 8762	.028	.71	.204	5.18	27
	3	7x28 TC	20003TSD Equal to Belden™ 8772	.033	.84	.218	5.54	35
18	2	16/30 TC	21802TSD Equal to Belden™ 8760	.028	.71	.222	5.64	32
	3	16/30 TC	21803TSD Equal to Belden™ 8770	.028	.71	.236	5.99	39
	4	19/30 TC	318004SD Equal to Belden™ 9418	.035	.89	.245	6.22	52
16	2	19x29 TC	21602SD Equal to Belden™ 8719	.032	.81	.313	7.95	52
14	2	19x27 TC	14002TSD Equal to Belden™ 8720	.035	.89	.330	8.38	63
12	2	19x25 TC	21202TSD Equal to Belden™ 8718	.034	.86	.400	10.2	95

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0419

Belden™ is a trademark of Belden Inc.



## PRODUCT DESCRIPTION

Polyethylene insulated stranded tinned copper conductors, short overall twist length, aluminum mylar shielding with drain wire and an overall gray PVC jacket.

#### **APPLICATIONS**

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

### **SPECIFICATIONS**

Conductor Stranded Tinned Copper Insulation Equal to competitor Jacket PVC Shield Aluminum Mylar

**NEC Articles** 

• 800 CM

• 14-12 AWG CL2

Voltage Rating 300 V Temp. Rating -25°C to 75°C

**Drain Wire** Equal to competitor

### **COLOR CODE CHART**

\*Equal to competitor

### **AVAILABLE PUT-UPS**

1,000' Reels and Boxes 500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

\*4-2402 and 4-2422 Are Constructed with a Tinned Copper Braid Shield