

SECURITY ALARM CABLE | LSHF UNSHIELDED



AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	7	412202	24	.015	.38	.116	2.95	10
	3	7	412203	24	.015	.38	.123	3.12	13
	4	7	412204	24	.015	.38	.134	3.40	16
	6	7	412206	24	.015	.38	.158	4.01	22
	8	7	412208	24	.015	.38	.169	4.29	28
	10	7	412210	24	.015	.38	.186	4.72	34
20	2	7	412002	25	.015	.38	.135	3.43	14
	3	7	412003	25	.015	.38	.143	3.63	18
	4	7	412004	25	.015	.38	.157	3.99	23
18	2	7	411802	27	.015	.38	.157	3.99	20
	3	7	411803	27	.015	.38	.168	4.27	26
	4	7	411804	27	.015	.38	.184	4.67	33
	5	7	411805	27	.015	.38	.193	4.90	40
	6	7	411806	27	.015	.38	.221	5.61	47
	7	7	411807	27	.015	.38	.221	5.61	53
	8	7	411808	27	.015	.38	.237	6.02	60
	9	7	411809	27	.015	.38	.249	6.32	67
	10	7	411810	27	.015	.38	.263	6.68	74
16	2	19	411602	31	.015	.38	.179	4.55	26
	3	19	411603	31	.015	.38	.191	4.85	35
	4	19	411604	31	.015	.38	.210	5.33	45
14	2	19	411402	30	.015	.38	.220	5.59	38
	3	19	411403	30	.015	.38	.236	5.99	54
12	4	19	411404	30	.015	.38	.260	6.60	69
	2	19	411202	33	.015	.38	.257	6.53	55
	4	19	411204	33	.015	.38	.305	7.75	102

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0622



(800) 343 2579 • www.adcable.com

PRODUCT DESCRIPTION

Low smoke halogen free polyolefin (LSHF) insulated stranded bare copper conductors, twisted with an overall gray LSHF polyolefin jacket* with rip cord.

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

SPECIFICATIONS

Conductor Stranded Bare Copper
Insulation Low Smoke Halogen Free Polyolefin

- 22 AWG .007"
- 20 AWG .008"
- 18-16 AWG .009"
- 14-12 AWG .012"

Jacket

- Low Smoke Halogen Free
- Polyolefin

NEC Articles

- 22-16 AWG: FPLR/760, CMR/800, CL3R/725
- 14-12 AWG: FPLR, CL3R

Voltage Rating 300 V

Temp. Rating -25°C to 90°C

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC c(UL)us CMR (UL)
 CL3R/FPLR-LSHF 90C E179335
 FT4/IEEE1202 RoHS

*14-12 AWG are not recognized by c(UL) or c(ETL).

*Other colors available upon request. Please consult factory for minimums and lead times.