

SECURITY ALARM CABLE | RISER SHIELDED



COMMUNICATION & CONTROL CABLES

AWG	COND	STRAND	PART NO.	CAP pF/FT	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
					INCH	mm	INCH	mm	
22	2	SOL	82202SDGY	53	.018	.46	.123	3.10	14
	2	7	12202RSD	53	.015	.38	.122	3.10	11
	3	7	12203RSD	53	.016	.38	.128	3.25	15
	4	SOL	82204SDGY	53	.018	.46	.140	3.56	19
	4	7	12204RSD	53	.015	.38	.138	3.51	19
	6	7	12206RSD	53	.015	.38	.166	4.22	29
	8	7	12208RSD	53	.015	.38	.180	4.57	32
	10	7	12210RSD	53	.015	.38	.202	5.13	38
20	12	7	12212RSD	53	.015	.38	.210	5.33	45
	2	7	12002RSD	54	.015	.38	.138	3.51	16
18	4	7	12004RSD	54	.015	.38	.159	4.04	26
	2	7	11802RSD	54	.015	.38	.165	4.19	22
	3	7	11803RSD	54	.015	.38	.167	4.24	30
	4	7	11804RSD	54	.015	.38	.192	4.88	37
	5	7	11805RSD	54	.015	.38	.203	5.16	45
	6	7	11806RSD	54	.015	.38	.230	5.84	50
	7	7	11807RSD	54	.015	.38	.230	5.84	57
	8	7	11808RSD	54	.015	.38	.247	6.27	64
	9	7	11809RSD	54	.015	.38	.261	6.63	71
	10	7	11810RSD	54	.015	.38	.284	7.21	72
16	12	7	11812RSD	54	.015	.38	.295	7.49	90
	2	19	11602RSD	64	.015	.38	.188	4.78	32
	3	19	11603RSD	64	.015	.38	.200	5.08	42
14	4	19	11604RSD	64	.015	.38	.220	5.59	52
	2	19	11402RSD	66	.015	.38	.226	5.74	40
12	3	19	11403RSD	66	.015	.38	.243	6.17	59
	4	19	11404RSD	66	.015	.38	.268	6.81	77
12	2	19	11202RSD	74	.015	.38	.266	6.76	61

The information contained on this specification is intended to be used as a guide and every effort has been made to ensure its accuracy at time of publication. This specification is subject to change anytime without notice. Please refer to www.adcable.com for the most up to date information. Rev 0622

PRODUCT DESCRIPTION

PVC insulated stranded bare copper conductors, twisted, aluminum mylar shielding with drain wire and an overall gray PVC jacket* with rip cord.

APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

SPECIFICATIONS

Conductor Bare Copper
Insulation

- 22 AWG .007"
- 20 AWG .008"
- 18-16 AWG .010"
- 14-12 AWG .012"

Shield Aluminum Mylar
Jacket PVC

NEC Articles

- 22-16 AWG: FPLR/760, CMR/800, CL3R/725
- 14-12 AWG: FPLR, CL3R

Voltage Rating 300 V

Temp. Rating -25°C to 75°C

COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

AVAILABLE PUT-UPS

1,000' Reels and Boxes

500' Reels and Boxes

Other lengths available. Please consult your factory representative for availability.

CABLE IDENTIFICATION

XX AWG XC SHIELDED (UL)
TYPE CL3R/FPLR c(UL)us TYPE
CMR E179335

*Other colors available upon request. Please consult factory for minimums and lead times.

*14-12 AWG are not recognized by c(UL).



(800) 343 2579 • www.adcable.com