


SIGNAL CABLE

IMSA Spec 19-1 • Solid Conductor



Cable Identification

Indent print on jacket
 “ADVANCED DIGITAL CABLE,
 INC. IMSA 19-1 YYYY* 600V”
 *replace YYYY with year of manufacture

Inkjet print on reverse side of
 jacket with footage markers.

Specifications		Color Code	Put-Ups
Conductor - Solid Bare Copper per ASTM B-3 Insulation 14 AWG - .025" (.635mm) PE 12 AWG - .030" (.762mm) PE	Jacket - PVC Voltage Rating - 600 V Temp. Rating - 75°C	Per Specification, See Color Code Tables on Page 15.	Standard Reels 2,500' and 5,000' <i>Other lengths available. Please consult your factory represen- tative for availability.</i>

PART NO.	NO. OF COND	OUTER JKT THICKNESS		NOMINAL O.D.		WEIGHT lbs. / 1M'
		INCH	mm	INCH	mm	
14 AWG						
8002	2	.045	1.143	.322	8.18	58
8003	3	.045	1.143	.339	8.61	75
8004	4	.045	1.143	.369	9.37	94
8005	5	.045	1.143	.402	10.21	113
8007	7	.045	1.143	.435	11.05	146
8009	9	.060	1.524	.538	13.67	186
8010	10	.060	1.524	.580	14.73	220
8012	12	.060	1.524	.597	15.16	254
8014	14	.060	1.524	.626	15.90	325
8015	15	.060	1.524	.660	16.76	311
8016	16	.060	1.524	.660	16.76	325
8019	19	.060	1.524	.694	17.63	375
8020	20	.060	1.524	.729	18.52	395
8021	21	.060	1.524	.729	18.52	413
8025	25	.060	1.524	.808	20.52	478
8026	26	.060	1.524	.808	20.52	501
12 AWG						
8402	2	.045	1.143	.376	9.55	58
8403	3	.045	1.143	.397	10.08	75
8404	4	.045	1.143	.434	11.02	94
8405	5	.045	1.143	.475	12.07	113
8407	7	.045	1.143	.514	13.06	146
8409	9	.060	1.524	.634	16.10	186
8410	10	.060	1.524	.688	17.48	220
8412	12	.060	1.524	.709	18.01	254
8416	16	.060	1.524	.787	19.99	325
8419	19	.060	1.524	.829	21.06	395
8420	20	.080	2.03	.913	23.19	631
8421	21	.080	2.03	.913	23.19	652
8425	25	.080	2.03	1.010	25.65	760

The information contained on this specification is intended to be used as a guide in product selection and is believed to be reliable. ADC has made every effort to ensure the data shown above is accurate at the time of publication. This specification is subject to change anytime without notice.